


S 2 TOIVAC

Flexible and very heavy weight ducting made of PE

- Applications** mobile toilets, sewage suction, waste disposal vehicles, waste water, sewage treatment plants
- Structure** PE, yellow / saffron yellow (similar RAL 1017), opaque, plastic spiral / PE
- Temperature** -40°C up to 60°C
- Properties** can be driven over, crush-resistant, good tensile strength, very high vacuum resistance, very good chemical resistance, weather proof, good ozone- & UV-resistance, hydrolysis & microbe resistant, rot proof
- Optional**
 - with tightly welded connection cuffs
 - cuffs also available individually



Inner Diameter (mm)	Outer Diameter (mm)	Wall Thickness (mm)	Bending Radius (mm)	Max. Operating Pressure (bar)	Vacuum Max. (bar)	Total Weight per Piece (kg)	Length (m)	Article Number
51	71,00	1,40	85	0,00	0,95	8,57	10	ND31005100K
51	71,00	1,40	85	0,00	0,95	12,85	15	ND31005100M
51	71,00	1,40	85	0,00	0,95	17,14	20	ND31005100N
63	83,00	1,40	105	0,00	0,95	12,24	10	ND31006300K
63	83,00	1,40	105	0,00	0,95	18,36	15	ND31006300M
63	83,00	1,40	105	0,00	0,95	24,48	20	ND31006300N
76	96,00	1,40	125	0,00	0,95	14,53	10	ND31007600K
76	96,00	1,40	125	0,00	0,95	21,79	15	ND31007600M
76	96,00	1,40	125	0,00	0,95	29,05	20	ND31007600N
102	122,00	1,40	165	0,00	0,85	19,10	10	ND31010200K