

# OnePress Germany 257

Flexible and robust compressed air hose with highly tear-resistant fabric insert

|                     |                                                                                                                                                 |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications</b> | compressed air, compressors, construction machines, pneumatics, automation technology & robotics                                                |
| <b>Structure</b>    | SBR, black, opaque                                                                                                                              |
| <b>Temperature</b>  | -20°C up to 100°C                                                                                                                               |
| <b>Properties</b>   | very high pressure resistance, crush-resistant, very good abrasion resistance, very smooth inside, smooth outside, good oil & petrol resistance |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Burst Pressure (bar) | Weight (kg/m) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|----------------------|---------------|-----------------------------|------------|----------------|
| 19                  | 31,00               | 6,00                | 240                 | 20,00                         | 60,00                | 0,65000       | 13,00                       | 20         | NS61201900N    |
| 25                  | 39,00               | 7,00                | 300                 | 20,00                         | 60,00                | 1,10000       | 44,00                       | 40         | NS61202500Y    |
| 25                  | 39,00               | 7,00                | 300                 | 20,00                         | 60,00                | 1,10000       | 22,00                       | 20         | NS61202500N    |