

S 5 PUR S EL

Medium weight and flexible spiral hose made of Polyurethane, electrically conductive

| | |
|---------------------|---|
| Applications | conveying of abrasive media, conveying technology, extraction systems, rail vehicles |
| Structure | TPU / Polyether-Polyurethane, black / jet black (similar RAL 9005), opaque, steel wire / spring steel wire / coated / PVC |
| Temperature | -40°C up to 90°C |
| Properties | good flexibility, electrically conductive ($R \leq 10^3 \text{ Ohm}$), very good abrasion resistance, good tensile strength, hydrolysis & microbe resistant |
| Norms | TRBS 2153/TRGS 727, ATEX 2014/34/EU / aspiration (no zone or inside: zone 22), ATEX 2014/34/EU / pneumatic transport of combustible dusts (inside: zone 20, 21, 22) |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|-------------------|-----------------------------|------------|----------------|
| 51 | 58,00 | 0,80 | 77 | 1,70 | 0,38 | 0,00 | 10 | ND53305150K |
| 51 | 58,00 | 0,80 | 77 | 1,70 | 0,38 | 0,00 | 15 | ND53305150M |
| 60 | 67,00 | 0,80 | 90 | 1,60 | 0,35 | 5,77 | 10 | ND53306050K |
| 60 | 67,00 | 0,80 | 90 | 1,60 | 0,35 | 8,66 | 15 | ND53306050M |
| 65 | 72,00 | 0,80 | 98 | 1,45 | 0,32 | 6,23 | 10 | ND53306550K |
| 65 | 72,00 | 0,80 | 98 | 1,45 | 0,32 | 9,35 | 15 | ND53306550M |
| 70 | 77,00 | 0,80 | 105 | 1,30 | 0,30 | 6,69 | 10 | ND53307050K |
| 70 | 77,00 | 0,80 | 105 | 1,30 | 0,30 | 10,04 | 15 | ND53307050M |
| 76 | 83,00 | 0,80 | 114 | 1,20 | 0,30 | 7,25 | 10 | ND53307650K |
| 76 | 83,00 | 0,80 | 114 | 1,20 | 0,30 | 10,87 | 15 | ND53307650M |
| 80 | 87,00 | 0,80 | 120 | 1,20 | 0,30 | 7,62 | 10 | ND53308000K |
| 80 | 87,00 | 0,80 | 120 | 1,20 | 0,30 | 11,43 | 15 | ND53308000M |
| 90 | 97,00 | 0,80 | 135 | 1,10 | 0,28 | 0,00 | 10 | ND53309000K |
| 90 | 97,00 | 0,80 | 135 | 1,10 | 0,28 | 0,00 | 15 | ND53309000M |
| 102 | 110,00 | 1,00 | 153 | 1,00 | 0,25 | 10,47 | 10 | ND53310250K |
| 102 | 110,00 | 1,00 | 153 | 1,00 | 0,25 | 15,71 | 15 | ND53310250M |
| 125 | 133,00 | 1,00 | 188 | 0,80 | 0,20 | 12,77 | 10 | ND53312550K |
| 125 | 133,00 | 1,00 | 188 | 0,80 | 0,20 | 19,16 | 15 | ND53312550M |
| 152 | 161,00 | 1,00 | 227 | 0,50 | 0,18 | 0,00 | 15 | ND53315250M |
| 152 | 161,00 | 1,00 | 227 | 0,50 | 0,18 | 0,00 | 10 | ND53315250K |
| 160 | 169,00 | 1,00 | 240 | 0,40 | 0,16 | 16,76 | 10 | ND53316050K |
| 160 | 169,00 | 1,00 | 240 | 0,40 | 0,16 | 25,14 | 15 | ND53316050M |

| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|-------------------|-----------------------------|------------|----------------|
| 180 | 189,00 | 1,00 | 270 | 0,30 | 0,15 | 18,78 | 10 | ND53318050K |
| 180 | 189,00 | 1,00 | 270 | 0,30 | 0,15 | 28,17 | 15 | ND53318050M |
| 200 | 209,00 | 1,00 | 315 | 0,25 | 0,13 | 20,80 | 10 | ND53320050K |
| 200 | 209,00 | 1,00 | 315 | 0,25 | 0,13 | 31,20 | 15 | ND53320050M |
| 250 | 263,00 | 1,00 | 375 | 0,20 | 0,12 | 30,87 | 10 | ND53325050K |