

## S 7 HYP-TEF EL

Highly flexible clip hose for suction of aggressive vapors, electrically conductive

|                     |                                                                                                                               |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications</b> | paint mist extraction, paper production, solvent vapor extraction, pharmaceutical production, air extraction                  |
| <b>Structure</b>    | Hypalon® coated polyester fabric, black / jet black (similar RAL 9005), opaque, clip profile / multi-layer                    |
| <b>Temperature</b>  | -40°C up to 175°C, short term up to 190°C                                                                                     |
| <b>Properties</b>   | light weight, very good flexibility, very good temperature resistance, very good chemical resistance, electrically conductive |
| <b>Norms</b>        | TRBS 2153, ATEX 2014/34/EU                                                                                                    |



| Inner Diameter (mm) | Outer Diameter (mm) | Wall Thickness (mm) | Bending Radius (mm) | Max. Operating Pressure (bar) | Vacuum Max. (bar) | Total Weight per Piece (kg) | Length (m) | Article Number |
|---------------------|---------------------|---------------------|---------------------|-------------------------------|-------------------|-----------------------------|------------|----------------|
| 76                  | 86,00               | 0,40                | 45                  | 0,60                          | 0,17              | 0,00                        | 3          | ND76207600B    |
| 76                  | 86,00               | 0,40                | 45                  | 0,60                          | 0,17              | 0,00                        | 6          | ND76207600G    |
| 102                 | 112,00              | 0,40                | 60                  | 0,50                          | 0,10              | 0,00                        | 3          | ND76210200B    |
| 102                 | 112,00              | 0,40                | 60                  | 0,50                          | 0,10              | 0,00                        | 6          | ND76210200G    |
| 127                 | 137,00              | 0,40                | 75                  | 0,32                          | 0,06              | 2,53                        | 3          | ND76212700B    |
| 127                 | 137,00              | 0,40                | 75                  | 0,32                          | 0,06              | 5,05                        | 6          | ND76212700G    |
| 152                 | 162,00              | 0,40                | 90                  | 0,22                          | 0,04              | 0,00                        | 6          | ND76215200G    |
| 152                 | 162,00              | 0,40                | 90                  | 0,22                          | 0,04              | 0,00                        | 3          | ND76215200B    |